

# Xerox® Instant Print Kiosk



## SYSTEM SPECIFICATIONS

Print Speed and Monthly Volume	Xerox® Instant Print Kiosk
Simplex Speed Color / B/W	Up to 50 / 55 ppm
Recommended Average Monthly Print Volume <sup>1</sup>	Up to 12,000 pages
Maximum Monthly Duty Cycle <sup>2</sup>	Up to 300,000 pages

<sup>1</sup> The Average Monthly Print Volume is the expected regular monthly throughput.

<sup>2</sup> The Monthly Duty Cycle is the maximum volume capacity expected in any one month. The volume is supported under standard vendor supplied service for any single month but is not expected to be sustained on a regular basis. Customers should consider higher volume machines or multiple machines if average monthly volume approaches the maximum duty cycle on a continual basis.

## DEVICE SPECIFICATIONS

Connectivity				
10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print				
User Interface Language Support				
US English				
Certifications				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				
Electrical Requirements				
Geographies: Western Hemisphere				
Line Option	Sole Use (not required but recommended)			
Voltage	110 -127 VAC			
Amperage	15 A			
Frequency	50/60 Hz, Single Phase			
Power Cord Length	8.5 feet			
Receptacle	NEMA part #: 5-15R Quantity – 2 1- IOT, 1-UI/Card Reader			
Operating Environment				
Required Temperature Range	50° to 82° F (10° to 28° C)			
Required Relative Humidity	15% to 85% RH			
Altitude (above sea level)	Max of 8,200 (2,500 meters)			
Sound Power Levels	Operating: 6.8 B(A) Standby: 3.6 B(A)			
Sound Pressure Levels	Operating: 55.8 dB(A) Standby: 18.5 dB(A)			
Audible Noise				
Sound Power Levels	Operating: 6.8 B(A) Standby: 3.6 B(A)			
Sound Pressure Levels	Operating: 55.9 dB(A) Standby: 18.5 dB(A)			
Dimensions and Weights				
Configuration	Width	Depth	Height	Weight
Including Office Finisher LX	46.5 in. / 1,182 mm	29.8 in. / 757 mm	45.2 in. / 1,149 mm	396 lbs. / 168 kg

## Feature Specifications

Print	
Resolution	Up to 1200 x 2400 dpi
Registration	Printing registration specifications for 8.5" x 11" (A4): ±1.5 mm (side 1), ±1.9 mm (side 2) along the lead edge ±2.0 mm (side 1), ±2.4 mm (side 2) along the side edge from Trays 1-4 Lead Edge is ±2.2 mm Skew registration specification from side-to-side feeding for 8.5 x 11" (A4): from Tray 1-4 is ±3 mm (side 1), ±4 mm (side 2)
Max Printable Area	The product will reproduce 11" x 17" full color. On all media there is a Lead Edge deletion of 4 mm and a Trail Edge deletion of 2 mm. The Side Edge deletion varies with paper size.
Print Features	Letter Color Print Letter B&W Print Legal Color Print Legal B&W Print Tabloid Color Print Tabloid B&W Print Stapling Hole Punch (optional)
Copy	
Sides	Input-to-Output: 1-1, 1-2, 2-2, 2-1
Quantity	1 to 999
Max. Resolution	Up to 600 x 600 dpi
Reduce/Enlarge	Variable zoom from 25% to 400% in 1% increments
Features	Letter Color Copy Letter B&W Copy Legal Color Copy Legal B&W Copy Tabloid Color Copy Tabloid B&W Copy Stapling Hole Punch (optional)
Scan	
Input Speed 8.5 x 11 in. / A4 LEF	Scan at up to 133 ipm for color or black-and-white
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color) Scan Default Resolution: 300 dpi
Max Scan Area	11 x 17 in.
Network Scan Protocol	HTTPS
File Formats	JPG Searchable PDF Encrypted / Password-protected PDF (Scan to Email only)
Scan Features	Standard: Scan to Email, Scan to USB, Scan to SharePoint™, Scan to Drop Box™, Scan to OneDrive™, Scan to Google Drive™ Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background Suppression 2- Sided Lighten/Darken Original Orientation (Portrait/Landscape)

## Xerox® Instant Print Kiosk

Security	
Security Features	<p>McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Services Engine (ISE) Integration, SSL, SNMPv3, Audit Log</p> <p>Expanded Authentication Secure Data</p> <ul style="list-style-type: none"> <li>• Encrypted Password Protected PDF (when using Scan to Email only)</li> <li>• Immediate Image Overwrite</li> <li>• On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk</li> <li>• FIPS 140-2 256-bit Hard Disk Encryption</li> </ul> <p>Expanded Authorization Secure Network Access IP Filter, IPsec, IPv6, SSL, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec integration (optional), Device Security</p> <ul style="list-style-type: none"> <li>• McAfee® Embedded Security, Port disablement including USB ports, Audit Log</li> </ul>
Remote Services	
Xerox® Meter-Assistant® Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® Supplies-Assistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Maintenance Assistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Controller / Print Server	
Processor	1.2 GHz Dual-core
Memory	2 GB system plus 1 GB page memory
System Disk	250 GB
Network Protocols	Administrative Protocols: DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP, DNS, SSDP

## SYSTEM PRODUCTIVITY

Size	Weight	Color / Black Speed	
		Simplex ppm	Duplex ppm
8.5 x 11 in. LEF	16lb. – 28 lb. Bond (60 gsm – 105 gsm)	50/55	50/55
11 x 17 in. SEF	16 lb. – 28 lb. Bond (60 gsm – 105 gsm)	25/27	18/19
8.5 x 14 in. SEF	16 lb. – 28 lb. Bond (60 gsm – 105 gsm)	29/32	19/21
8.5 x 11 in. LEF	Lightweight Cardstock 28 lb. Bond – 90 lb. Index (106 gsm – 169 gsm)	32/32	32/32
11 x 17 in. SEF	Lightweight Cardstock 28 lb. Bond – 90 lb. Index (106 gsm – 169 gsm)	17/17	13/13
8.5 x 14 in. SEF	Lightweight Cardstock 28 lb. Bond – 90 lb. Index (106 gsm – 169 gsm)	20/20	15/15
8.5 x 11 in. LEF	Gloss 80 lb. Text – 100 lb. Text (106 gsm – 169 gsm)	32/32	32/32
11 x 17 in. SEF	Gloss 80 lb. Text – 100 lb. Text (106 gsm – 169 gsm)	17/17	13/13
8.5 x 14 in. SEF	Gloss 80 lb. Text – 100 lb. Text (106 gsm – 169 gsm)	20/20	15/15
8.5 x 11 in. LEF	Cardstock 65 lb. Cover – 140 lb. Index (170 gsm – 256 gsm) and Heavyweight Cardstock 140 lb. Index – 110 lb. Cover (257 gsm – 300 gsm)	22/22	22/22*

11 x 17 in. SEF	Cardstock 65 lb. Cover – 140 lb. Index (170gsm – 256 gsm) and Heavyweight Cardstock 140 lb. Index – 110 lb. Cover (257 gsm – 300 gsm)	13/13	9/9*
8.5 x 14 in. SEF	Cardstock 65 lb. Cover – 140 lb. Index (170 gsm – 256 gsm) and Heavyweight Cardstock 140 lb. Index – 110 lb. Cover (257 gsm – 300 gsm)	15/15	10/10*
8.5 x 11 in. LEF	Glossy Cardstock 65 lb. Cover – 140 lb. Index (170 gsm – 256 gsm) and Heavy Glossy Cardstock 140 lb. Index – 110 lb. Cover (257 gsm – 300 gsm)	22/22	22/22*
11 x 17 in. SEF	Glossy Cardstock 65 lb. Cover – 140 lb. Index (170 gsm – 256 gsm) and Heavy Glossy Cardstock 140 lb. Index – 110 lb. Cover (257 gsm – 300 gsm)	13/13	9/9*
8.5 x 14 in. SEF	Glossy Cardstock 65 lb. Cover – 140 lb. Index (170 gsm – 256 gsm) and Heavy Glossy Cardstock 140 lb. Index – 110 lb. Cover (257 gsm – 300 gsm)	15/15	10/10*

\* Auto Duplex capable up to 80 lb. Cover / 220 gsm max or 169 gsm coated paper

LEF = Long edge feed; SEF = Short edge feed

Note: Heavy and Glossy papers may result in increased image mottle. It is recommended that high-quality papers available through Xerox, with even paper formation, be used to minimize the amount of mottle.

## FEEDING SPECIFICATIONS

Duplex Automatic Document Feeder	
Capacity <sup>3</sup>	130 sheets (Single-pass DADF)
Speed	Up to 80 images per minute black-and-white and color (simplex) Up to 133 images per minute black-and-white and color (duplex)
Paper Sizes Sensed	8.5 x 11 in. to 11 x 17 in.
Weights	16 lb. bond to 32 lb. bond / 60 gsm to 128 gsm
Trays (Total 3,040 sheets)	
Capacity	Tray 1: 520 sheets Tray 2: 520 sheets Tray 3: 867 sheets Tray 4: 1,133 sheets Tray 5: 100 sheets
Standard Sizes	Tray 1 & 2: 8.5 x 11 in. to 11 x 17 in. Tray 3 & 4: 8.5 x 11 in.
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
*Supported Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted
*Admin support required	

<sup>3</sup>When using Xerox® Vitality™ Multipurpose Printer Paper (20 lb. / 80 gsm)

## FINISHING SPECIFICATIONS

Output Trays		
Stacking Tray	Left-side Face-up Tray – up to 100 sheets	
Office Finisher LX		
Capacity	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in.)	
Sizes	8.5 x 11 in. to 11 x 17 in.	
Weights	16 lb. bond to 80 lb. cover / 60 gsm to 256 gsm	
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm	
Hole Punch (Optional)	2-3 Hole Punch	
	Up to 65 lb. cover (176 gsm)	
Supplies and Consumables	Reorder #	Units per Carton
Black Toner Cartridge Metered	006R01509	1 Cartridge
Yellow Toner Cartridge Metered	006R01510	1 Cartridge
Magenta Toner Cartridge Metered	006R01511	1 Cartridge
Cyan Toner Cartridge Metered	006R01512	1 Cartridge
Black Toner Cartridge Sold	006R01513	1 Cartridge
Yellow Toner Cartridge Sold	006R01514	1 Cartridge
Magenta Toner Cartridge Sold	006R01515	1 Cartridge
Cyan Toner Cartridge Sold	006R01516	1 Cartridge
Drum Cartridge	13R00662	1 Cartridge
Transfer Belt Cleaner	1R00613	1 Assembly
Second Bias Transfer Roll	8R13064	1 Assembly
Waste Toner Container	8R13061	1 Cartridge
Staple Refills – Office Finisher LX	8R12941	3 Refills
Staple Cartridge – Office Finisher LX	8R12964	1 Cartridge

For more information, visit us at [www.xerox.com/office](http://www.xerox.com/office).

